

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

1 Identification

- **Product identifier**
- **Trade name:** HISTOSOL - XYLENE SUBSTITUTE
- **Article number:** 23405-01, 23405-04
- **CAS Number:**
64742-95-6
- **EC number:**
265-199-0
- **Index number:**
649-356-00-4
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Electron Microscopy Sciences
1560 Industry Road
USA-Hatfield, PA 19440
Tel: 215-412-8400 Fax: 215-412-8450
email: info@emsdiasum.com
www.emsdiasum.com
- **Information department:** Product safety department
- **Emergency telephone number:**
ChemTrec 1-800-424-9300 Contract CCN7661
1-703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Flammable Liquids 4

H227 Combustible liquid.

- **Label elements**
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Solvent naphtha (petroleum), light arom.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 1)

- **Hazard statements**

Combustible liquid.
Harmful if inhaled.
May cause respiratory irritation.
May be fatal if swallowed and enters airways.

- **Precautionary statements**

Keep away from flames and hot surfaces. – No smoking.
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**

- **CAS No. Description**

64742-95-6 Solvent naphtha (petroleum), light arom.

- **Identification number(s)**

- **EC number:** 265-199-0

- **Index number:** 649-356-00-4

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 2)

- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**
Substance is not listed.

· **PAC-2:**
Substance is not listed.

· **PAC-3:**
Substance is not listed.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:** Not required.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
 - **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
- **Form:** Liquid
- **Color:** Colorless
- **Odor:** Aromatic
- **Odor threshold:** Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 4)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-50 °C (-58 °F)
Boiling point/Boiling range:	162 °C (323.6 °F)
· Flash point:	>61 °C (>141.8 °F)
· Flammability (solid, gaseous):	Not flammable.
· Ignition temperature:	450 °C (842 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	5 hPa (3.8 mm Hg)
· Density at 20 °C (68 °F):	3.5 g/cm ³ (29.2075 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	0.05 g/l
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	100.0 %
VOC content:	100.00 %
	3,500.0 g/l / 29.21 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: **HISTOSOL - XYLENE SUBSTITUTE**

(Contd. of page 5)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

Substance is not listed.

- **NTP (National Toxicology Program)**

Substance is not listed.

- **OSHA-Ca (Occupational Safety Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Toxic for fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023




Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT · ADR, IMDG, IATA 	<p style="margin-left: 20px;">Void</p> <p style="margin-left: 20px;">UN1268</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG · IATA 	<p style="margin-left: 20px;">Void</p> <p style="margin-left: 20px;">1268 PETROLEUM PRODUCTS, N.O.S., ENVIRONMENTALLY HAZARDOUS</p> <p style="margin-left: 20px;">PETROLEUM PRODUCTS, N.O.S., MARINE POLLUTANT</p> <p style="margin-left: 20px;">PETROLEUM PRODUCTS, N.O.S.</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT · Class 	<p style="margin-left: 20px;">Void</p>
<ul style="list-style-type: none"> · ADR, IMDG <div style="display: flex; align-items: center; gap: 10px;">   </div>	<ul style="list-style-type: none"> · Class · Label <p style="margin-left: 20px;">3 Flammable liquids</p> <p style="margin-left: 20px;">3</p>
<ul style="list-style-type: none"> · IATA <div style="display: flex; align-items: center; gap: 10px;">  </div>	<ul style="list-style-type: none"> · Class · Label <p style="margin-left: 20px;">3 Flammable liquids</p> <p style="margin-left: 20px;">3</p>
<ul style="list-style-type: none"> · Packing group · DOT · ADR, IMDG, IATA 	<p style="margin-left: 20px;">Void</p> <p style="margin-left: 20px;">III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: · Special marking (ADR): 	<p style="margin-left: 20px;">Symbol (fish and tree)</p> <p style="margin-left: 20px;">Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · Special precautions for user · Stowage Category 	<p style="margin-left: 20px;">Warning: Flammable liquids</p> <p style="margin-left: 20px;">A</p>

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: **HISTOSOL - XYLENE SUBSTITUTE**

(Contd. of page 7)

· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1268 PETROLEUM PRODUCTS, N.O.S. 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is not listed.

· **TSCA (Toxic Substances Control Act):**

Substance is not listed.

· **Hazardous Air Pollutants**

Substance is not listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

Substance is not listed.

· **TLV (Threshold Limit Value)**

Substance is not listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

· **Hazard statements**

Combustible liquid.

Harmful if inhaled.

May cause respiratory irritation.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from flames and hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 01/31/2023

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/31/2023

Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 9)

*NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Flammable Liquids 4: Flammable liquids – Category 4**Acute Toxicity - Inhalation 4: Acute toxicity – Category 4**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3**Aspiration Hazard 1: Aspiration hazard – Category 1*

-US-